

Automatic Bollards – B3300

Operation Type: Electric/Pneumatic/Hydraulic



PRODUCT OVERVIEW

BGI B3300 Security Automatic Bollards Is electric or pneumatic or hydraulic operated.

Able to cope with a high number of operations per hour, this product can be a part of a large, secure access control scheme or operated as a standalone system.

The control board provided as standard is a plc control system which we can setup to meet whatever operational requirements you may have (push button, touch screen, card reader, LPR....).

Safety: we recommended for each project to choose the correct safety devices. like: Loop detector, photocell eyes, Traffic Light, a synchronize Arm Barrier.

Finish: Galvanized as standard with stainless steel cover, optional Led Light strip at the top.

B3300 Automatic Bollard

| | |
|---------------------|---|
| Bollard Diameter | 270 mm |
| Height Above Ground | 900 mm |
| Foundation Depth | 1500-1750 mm |
| Finishes Available | Supplied with stainless steel cover. Optional Led Strip on top |
| Mechanism | <ul style="list-style-type: none">• Electric – internal unit in each Bollard• Pneumatic- External Compressor• Hydraulic- External HPU |
| Security Rating | K8: 7,500 kg vehicle travelling at 64 kph. |

BGI Product Range

- **Automatic Bollard K4/K8/K12**
- Road Block
- Security Arm Barrier
- Full Height Turnstile
- Automatic/Static Spikes
- Automatic Gates
- Fix Bollards /Shallow Mount Bollards

