

# SP30 HIGH SECURITY FIXED BOLLARD

Operation Type: Static Security Bollard



## PRODUCT OVERVIEW

The ATG Access, Fixed SP30 Bollard is a tall and slim product offering site security rated to withstand a 7,500 kg vehicle travelling at 48 kph. Galvanised as standard, the bollard is also supplied with two yellow reflective bands. Alternatively, the bollard can be nylon coated to any RAL colour specified or fitted with a decorative sleeve.

This product provides a cost-effective solution for perimeter security requirements and meets the security rating for most perimeter security projects.

ATG Access has a variety of complimentary automatic, lift-out or manually retractable products for additional vehicle access requirements in order to provide a holistic perimeter

security offering.

Successfully impact tested to 48 kph using a 7,500 kg vehicle and achieving zero penetration, this product is only available as a traditional foundation, fixed bollard.

Must be installed within an approved, reinforced concrete foundation which includes a rebar structure; supplied in 1,655 mm overall tube length.

For sites requiring perimeter protection with limited excavation depth available, ATG Access's range of shallow foundation fixed bollards may be more suitable; available with depths as little as 40 mm.

## SECURITY RATING

Meets the BSI PAS 68 rating when installed to the PAS 69 certification.

V/7,500(N2)/48/90:0/0

## FINISHES

Available in a variety of finishes: galvanised, painted to any specified RAL colour or fitted with an aesthetic sleeve to suit client requirements.

## SP40 HIGH SECURITY FIXED BOLLARD

	Fixed
Bollard Diameter	219 mm
Height Above Ground	1,000 mm
Foundation Depth	655 mm (1,655 mm overall length)
Finishes Available	Galvanised as standard; can be coated to a specified RAL colour or fitted with an aesthetic sleeve.
Security Rating	V/7,500(N2)/48/90:0/0

