

SP40 HIGH SECURITY FIXED BOLLARD

Operation Type: Fixed Security Bollard



PRODUCT OVERVIEW

The ATG Access High Security Fixed SP40 Bollard is a tall and slim product; offering a galvanised finish as standard. Alternatively, the bollard can be coated to any RAL colour specified or fitted with a decorative sleeve.

This product provides a cost-effective solution for perimeter security requirements and meets the security rating for most perimeter security projects.

ATG Access has a variety of complimentary automatic, lift-out or manually retractable products for additional vehicle access requirements in order to provide a holistic perimeter security offering.

SP40 FIXED BOLLARD

Successfully impact tested to 64 kph with a 7,500 kg vehicle, this product is perfect for both urban and industrial security scenarios.

Only available in a fixed variation, this product must be installed within an approved, reinforced concrete foundation. Supplied in an overall length of 1,655 mm and must be installed to comply with the PAS 69 1.2 m spacing requirements.

For sites requiring perimeter protection with limited excavation depth available, ATG Access's range of shallow foundation fixed bollards may be more suitable.

SECURITY RATING

Meets the BSI PAS 68 rating when installed to the PAS 69 certification.

V/7,500(N2)/64/90:4.0/16.7

FINISHES

Available in a variety of finishes: galvanised, painted to any specified RAL colour or fitted with an aesthetic sleeve to suit client requirements.

SP40 HIGH SECURITY FIXED BOLLARD

	Fixed
Bollard Diameter	219 mm
Height Above Ground	1,000 mm
Foundation Depth	655 mm (1,655 mm overall length)
Finishes Available	Galvanised. Painted to a specified RAL colour or fitted with an aesthetic sleeve
Security Rating	V/7,500(N2)/64/90:4.0/16.7

