

SP50 HIGH SECURITY FIXED BOLLARD

Operation Type: Fixed Security Bollard



PRODUCT OVERVIEW

ATG Access's High Security, Fixed SP50 Bollard is a cost-effective solution for providing certified perimeter protection against high velocity attacks.

The product is supplied hot dip galvanised as standard with two yellow reflective bands. Alternatively, the bollard can be coated with any RAL colour required or fitted with a decorative sleeve.

ATG Access has a variety of complimentary automatic, lift-out or manually retractable products for additional vehicle access requirements in order to provide a holistic perimeter security offering.

The ATG Access SP50 is a fixed high security bollard which has been successfully impact tested to 80 kph using a 7,500 kg vehicle.

Only available in a fixed variation, this product must be installed within an approved, reinforced concrete foundation. Supplied in an overall length of 1,650 mm; this product must be installed according to PAS 69 with 1.2 m spacings.

For sites requiring perimeter protection with limited excavation depth available, ATG Access's range of shallow foundation fixed bollards may be more suitable.

SECURITY RATING

Meets the BSI PAS 68 rating when installed to the PAS 69 certification.

V/7,500(N3)/80/90:10.6/11.1

FINISHES

Available in a variety of finishes: galvanised, painted to any specified RAL colour or fitted with an aesthetic sleeve to suit client requirements.

SP50 HIGH SECURITY FIXED BOLLARD

Fixed

Bollard Diameter	273 mm
Height Above Ground	1,080 mm
Foundation Depth	570 mm (overall length, 1,650 mm)
Finishes Available	Galvanised. Painted to a specified RAL colour or fitted with an aesthetic sleeve
Security Rating	V/7,500(N3)/80/90:10.6/11.1

