

Automatic Bollards – B3200

Operation Type: Electric/Pneumatic/Hydraulic



PRODUCT OVERVIEW

BGI B3200 Security Automatic Bollards Is electric or pneumatic or hydraulic operated.

Able to cope with a high number of operations per hour, this product can be a part of a large, secure access control scheme or operated as a standalone system.

The control board provided as standard is a plc control system which we can setup to meet whatever operational requirements you may have (push button, touch screen, card reader, LPR, etc).

Safety: we recommended for each project to choose the correct safety devices. like: Loop detector, photocell eyes, Traffic Light, a synchronize Arm Barrier.

Finish: Galvanized as standard with stainless steel cover, optional Led Light strip at the top.

B3200 Automatic Bollard	
Bollard Diameter	219 mm
Height Above Ground	700 mm
Foundation Depth	1250-1450 mm
Finishes Available	Supplied with stainless steel cover. Optional Led Strip on top
Mechanism	<ul style="list-style-type: none">• Electric – internal unit in each Bollard• Pneumatic- External Compressor• Hydraulic- External HPU
Security Rating	K4: 7,500 kg vehicle travelling at 48 kph.

BGI Product Range

- **Automatic Bollard K4/K8/K12**
- **Road Block**
- **Security Arm Barrier**
- **Full Height Turnstile**
- **Automatic/Static Spikes**
- **Automatic Gates**
- **Fix Bollards /Shallow Mount Bollards**

