Automatic Bollards - B5000

Operation Type: Electric/Hydraulic





PRODUCT OVERVIEW

BGI B5000 Security Automatic Bollards

Able to cope with a high number of operations per hour, this product can be a part of a large, secure access control scheme or operated as a standalone system.

The control board provided as standard is a plc control system which we can setup to meet whatever operational requirements you may have (push button, touch screen, card reader, LPR ,etc.

Safety: we recommended for each project to choose the correct safety devices. like: Loop detector, photocell eyes, Traffic Light, a synchronize Arm Barrier.

Finish: Galvanized as standard with stainless steel cover, optional Led Light strip at the top.

B5000 Automatic Bollard	
Bollard Diameter	350 mm
Height Above Ground	1000-1200 mm
Foundation Depth	1900-2300 mm
Finishes Available	Optional stainless steel cover. Optional Led Strip on top
Mechanism	 Electric – internal unit in each Bollard Hydraulic- External HPU
Security Rating	K12 -Pas 68 : V7,500 kg vehicle travelling at 80 kph. PAS 68 : V/7500(N3) /80/90:2.6/0.0

BGI Product Range

- Automatic Bollard K4/K8/K12
- Road Block
- Security Arm Barrier
- Full Heigh Turnstile
- Automatic/Static Spikes
- Automatic Gates
- Fix Bollards /Shallow Mount Bollards

